



Printing and Application Instructions

- 1) Copy/Print on to the coated side of the media using compatible Inkjet Printer.
- 2) To prevent a paper jam, make sure the vinyl is not bent or warped or corners folded BEFORE loading. Loading by hand ONE SHEET at the time (pressing FF/Ready) is a way to make sure it loads correctly.
- 3) When gluing a vinyl label to any surface, clean the surface and remove residual grease, soot or dust.

If the label is used outdoors you must use clear spray and overlaminate. The Overlaminates must be applied in such way that it prevents water from contacting the label. Clear enamel spray is available in most hardware or automotive parts stores.

HYAZ™ Inkjet Media

WHITE Inkjet Ultra Cling

Item #	UCFW8511
Media	Ultra Cling Film
Media Type	Inkjet
Color	White
Printers	All Inkjet Desk Top Printers
Type of Adhesive	Ultra Removable

For Car window we strongly recommend The Clear Ultra Cling as static cling can sometimes fall off glass surfaces that have been cleaned at one time or another with some cleaning agents that include anti fogging and or streak free agents. The UCF (Ultra Cling Film) works in the same way as the static cling but it has a new generation *micro spear coating* that clings to more types of substrates than static cling.

To extend UV resistant of Inkjet media HPS offers overlaminates with built in UV barrier.

For more general information see the back of this page.

Printer Settings



HPS PO Box 855
Rhome TX 76078-0855
sales@papilio.com
www.papilio.com

If your printer is not listed here then select transparency and normal resolution.

CANON 600 SERIES	CANON 4000 SERIES	EPSON PHOTO EX	EPSON 400, 600, 700, 800, 1520, 3000, 5000 SERIES & STYLUS	EPSON 400, 600, 700, 800, 1520, 3000, 5000 SERIES & STYLUS	HEWLETT PACKARD 600, 700, 800, 1000 & PHOTOSMART PRINTERS
Media Choice: High Res. Paper	Media Choice: High Res. Paper	Media Type: 360 dpi Ink Jet Paper	Media Type: 360 dpi Ink Jet Paper	Media Type: 360 dpi Ink Jet Paper	Media Type: Premium Ink Jet Paper
Print Quality: Photographic	Quality: Photographic	Print Quality: Photo	Print Quality: Photo	Print Quality: Photo	Print Quality: Photo
Resolution: Normal	Resolution: Standard				

For complete updated list of our media and to place an order online go to www.texascraft.com.

Disclaimer: We have tested our media in various personal inkjet printers with good results. The user of this paper/film must determine the suitability of this product before beginning production, using his equipment and method of application. The sellers and manufacturers maximum obligation shall be to replace paper/film that has been found to be defective. Neither the manufacturer nor the seller shall be held liable for any injury, direct or consequential, arising out of the use of, or inability to use this paper/film.

The UCF film is intended for indoor use only but may in some cases be used temporarily outdoors. We consider using any media inside automobile an outdoor use because of moisture and extreme temperature changes.

If this media is to be used indoors where steam or moisture is present then the artwork once printed must be protected with clear spray. For Car windows we strongly recommend the UCF media As static cling can sometimes fall off glass surfaces that have been cleaned at one time or another with some cleaning agents that include anti fogging and or streak free agents.

(We recommend Krylon Crystal Clear spray available at Wal-Mart, or Rust-Oleum available at Home Depot or similar product from another source)

Printing:

- 1) Copy/Print on to the coated side of the media using compatible printer.
- 2) To prevent a paper jam, make sure the sheet is not bent or warped or corners folded BEFORE loading. Loading by hand ONE SHEET at the time is a way to make sure it loads correctly. For this media it is important to select the correct printer driver setting. In general the transparency setting or glossy photo film setting (not paper) will work best. Depending on the Inkjet printer and ink used the label may be ready for use in as little as few minutes. In some cases you may have to allow the ink to dry for several hours or over night. Some universal refill inks may NOT work with this media.

Mounting:

- 1) When mounting this label to any surface, clean the substrate and remove residual grease, soot or dust. This media uses new type of tacky film (micro spears) to adhere to most substrates even carboard, wallpaper, smooth wood etc.
- 2) Peel the film GENTLY off the supporting paper in such way that you avoid stretching the media.
- 3) Line up your label. When the position looks correct, let the label make contact with the surface on one edge and work down the rest of the surface using your fingers. Do not use excessive pressure when working the label in this way because you may smudge the ink.

Tip: To make Ultra cling labels for automobile windows or when you want the label to be visible from the other side of a window or glass door. Follow the steps here above with two exceptions. Note: You must be using the CLEAR Ultra Cling. A) Print mirror image B) Spray the whole sheet with WHITE acrylic paint when the ink is dry. C) Let the paint dry. D) Follow mounting instructions here above.

For Car window we strongly recommend the UCF media as static cling can sometimes fall off glass surfaces that have been cleaned at one time or another with a cleaning agent(s) that include anti-fogging and or streak free agents. The UCF (Ultra Cling Film works in the same way as the static cling but has new generation micro spear tack coating that cling to the glass.

You can spray the label before you apply it (after printing) to prevent over spray. Fixative spray is available in most craft stores or you can use spray sold in most automotive parts stores. Using clear spray as the only protection will offer limited water proofing. If the label is to be used outdoors we recommend using our WOL overlamine together with the spray.

To extend UV resistant of Inkjet media HPS offers overlamine with built in UV barrier.

Ultra cling can be used on almost any substrate where as Static Cling must be used on glass or glossy finished items only. Papilio Ultra Cling has one side coated with inkjet coating and the other side coated with special cling substance that uses special "micro-spear technology" to CLING to substrates. This technology is similar to regular adhesive but when it is time to remove the label it can be peeled safely off almost any substrate. This media is in fact similar to our Cling Tack Media but is more advanced and safer on delicate substrates than ultra low peel adhesive.

The Ultra Cling is available Clear and White.

Please go to our web-site for more information or to order.
www.papilio.com